

MAC
INTERNATIONAL

THE
MAC AVANT
MOBILE PRESSURE WASHER RANGE



THE UK'S PREMIER CLEANING EQUIPMENT SUPPLIER

WWW.MACINTERNATIONAL.CO.UK

MAC AVANT RANGE

HOT MOBILE PRESSURE WASHER

**THE NUMBER
ONE INDUSTRIAL
PRESSURE WASHER**

- Highly professional hot pressure washer
- Perfect for all heavy-duty industrial applications
- High flow rate and pressure
- Steam stage with low pressure steam valve
- Proven reliability



30 SECOND
AUTO STOP/START



HIGH EFFICIENCY BOILER SYSTEM
AS STANDARD



SIMPLE CONTROLS



ANTI-SHOCK RUBBER WHEELS

THE MAC AVANT: COMPLETE WITH A FULL HOST OF MARKET LEADING INDUSTRIAL FEATURES



IMAGE SHOWS AVANT WITH STAINLESS STEEL HOSE REEL AND LANCE HOLDER

STANDARD FEATURES

- Heavy-duty steel chassis
- Stainless steel cover
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motor
- Automatic stop/start system
- MAC high efficiency boiler system
- 4 large anti-shock rubber wheels for tough terrain
- Large 31ltr easy fill fuel tank with low level sensor
- Water break tank with type AB airgap
- High pressure chemical system
- Plastic lance holder
- Steam stage with low pressure steam valve
- Bypass valve and safety valve
- Pressure gauge
- Burner control with flow switch and thermostat
- 24v low tension safety controls
- Low level fuel warning lamp with burner shutdown
- Mains power on lamp
- Including 10mt high pressure hose, single lance and RL37 washgun with swivel

	MAC1	MAC5	MAC49	MAC7
Water Flow	12lt per minute	15lt per minute	21lt per minute	9lt per minute
Pressure	100bar, 1500psi	200bar, 3000psi	200bar, 3000psi	100bar, 1500psi
Motor Specification	3hp, 1450rpm	7.5hp, 1450rpm	10hp, 1450rpm	3hp, 1450rpm
Chemical	High Pressure	High Pressure	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Temperature	0-150°C	0-150°C	0-150°C	0-150°C
Power	240v	415v	415v	110v
Weight	120kg	130kg	140kg	120kg
Dimensions (h x w x d)	85 x 63 x 100cm	85 x 63 x 100cm	85 x 63 x 100cm	85 x 63 x 100cm



DOWNLOAD THE DATASHEET FOR FULL SPECIFICATION AT WWW.MACINTERNATIONAL.CO.UK

MAC AVANT GRP

HOT MOBILE PRESSURE WASHER

30 SECOND
AUTO STOP/START



THE AVANT WITH GRP PLASTIC COVER

- Highly professional hot pressure washer
- Full Avant specification
- 240v, 415v & 110v options
- Strong GRP plastic cover
- Proven Avant reliability & performance

	MAC3	MAC4	MAC49/GRP	MAC7/GRP
Water Flow	12lt per minute	15lt per minute	21lt per minute	9lt per minute
Pressure	100bar, 1500psi	200bar, 3000psi	200bar, 3000psi	100bar, 1500psi
Motor Specification	3hp, 1450rpm	7.5hp, 1450rpm	10hp, 1450rpm	3hp, 1450rpm
Chemical	High Pressure	High Pressure	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Temperature	0-150°C	0-150°C	0-150°C	0-150°C
Power	240v	415v	415v	110v
Weight	110kg	120kg	140kg	110kg
Dimensions (h x w x d)	85 x 63 x 100cm	85 x 63 x 100cm	85 x 63 x 100cm	85 x 63 x 100cm



DOWNLOAD THE DATASHEET FOR FULL SPECIFICATION
AT WWW.MACINTERNATIONAL.CO.UK

MAC AVANT K SERIES

HOT MOBILE PRESSURE WASHER



THE AVANT ZERO PRESSURE RANGE

- Highly professional hot pressure washer
- Perfect for all heavy-duty and industrial hot water washing
- 240v or 415v options available
- Timed shutdown system

	MAC8	MAC10
Water Flow	12lt per minute	15lt per minute
Pressure	100bar, 1500psi	200bar, 3000psi
Motor Specification	3hp, 1450rpm	7.5hp, 1450rpm
Chemical	High Pressure	High Pressure
Shutdown System	Timed Shutdown – Zero Pressure	Timed Shutdown – Zero Pressure
Temperature	0-150°C	0-150°C
Power	240v	415v
Weight	120kg	130kg
Dimensions (h x w x d)	85 x 63 x 100cm	85 x 63 x 100cm



DOWNLOAD THE DATASHEET FOR FULL SPECIFICATION
AT WWW.MACINTERNATIONAL.CO.UK

MAC AVANT XL

HOT MOBILE PRESSURE WASHER

FLAME FAILURE AND
LEAK DETECTION
SYSTEM



THE AVANT XL HEAVY-DUTY

- Heavy-duty machine construction
- Highly professional hot pressure washer
- Flame failure & leak detection
- MAC high efficiency boiler system
- Stainless steel hinged cover
- Double bearing 10hp motor for high usage

MAC49XL

Water Flow	21lt per minute
Pressure	200bar, 3000psi
Motor Specification	10hp, 1450rpm Double Bearing
Chemical	High Pressure
Shutdown System	Auto Stop/Start
Shutdown System	Flame Failure & Leak Detection
Temperature	0-150°C
Power	415v
Weight	200kg
Dimensions (h x w x d)	98 x 66 x 113cm



DOWNLOAD THE DATASHEET FOR FULL SPECIFICATION
AT WWW.MACINTERNATIONAL.CO.UK

MAC AVANT OPTIONAL ACCESSORIES



AVANT/ACC001
STAINLESS STEEL
HOSE REEL KIT
20mt manual hose reel
with mounting kit



AVANT/ACC004
FROST PROTECTION
Including 60 watt heater tube
& thermostat



AVANT/ACC002
STAINLESS STEEL
LANCE HOLDER
Fitted



AVANT/ACC005
6LT STAINLESS STEEL
BREAK WATER TANK
Including float valve, fittings, type AB
airgap, fitted to machine



AVANT/ACC003
FLAME FAILURE &
LEAK DETECTION 
With photo cell and PCB upgrade
and fitting



AVANT/ACC006
TST (TOTAL STOP TIMER)
SYSTEM



MOBILE PRESSURE WASHERS
STATIC PRESSURE WASHERS
FLOORCARE



MANUFACTURED IN THE UK