

# MAC PLANTMASTER S.S.

## PREMIUM HOT STATIC PRESSURE WASHER

### THE PREMIUM STAINLESS STEEL OPTION FROM MAC

- Highly professional hot static pressure washer
- Featuring the new MAC 21TECH control system
- High specification with a full range of features
- Perfect for daily heavy-duty industrial cleaning
- CE approved and manufactured in the UK



### MAC 21TECH

USER FRIENDLY CONTROL SYSTEM

#### FEATURES

- Variable total timed shutdown
- Variable leak detection
- Advanced flame monitoring and control
- Low water protection
- Built in hour counter
- Fully bespoke design function - Siemens PLC

**SIEMENS**

**NEW FOR 2021**



#### KEY SPECIFICATION

Hot Water Static

12lt, 15lt or 21lt/min Water Flow

100bar or 200bar Pressure

230v or 400v Power Supply

Automatic Stop/Start

MAC 21TECH Control System

# MAC PLANTMASTER S.S.

## PREMIUM HOT STATIC PRESSURE WASHER



**THE MAC PLANTMASTER IS AVAILABLE IN FULL STAINLESS STEEL TO MEET THE GROWING DEMAND FOR QUALITY AND DURABILITY.**

### STANDARD FEATURES

- High quality, full stainless steel cabinet
- Lockable stainless steel front door
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motor
- Automatic stop/start system
- MAC high efficiency boiler system
- Full frost protection and cabinet insulation
- Internal break water tank
- 31lt easy fill fuel tank with low level sensor
- High pressure chemical system
- Burner control with ST7 flow switch and thermostat
- 24v low tension safety controls
- Lockable control panel

**CHOOSE FROM A WHOLE HOST OF BESPOKE OPTIONS WITH THE NEW MAC 21TECH CONTROL SYSTEM**

**MANUFACTURED IN GREAT BRITAIN** 

	21T/PLANTMASTER/SS1	21T/PLANTMASTER/SS3	21T/PLANTMASTER/SS4
Water Flow	12lt per minute	15lt per minute	21lt per minute
Pressure	100bar, 1500psi	200bar, 3000psi	200bar, 3000psi
Motor Specification	3hp, 2.2kw, 1450rpm	7.5hp, 5.5kw, 1450rpm	10hp, 7.5kw, 1450rpm
Chemical	High Pressure	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Temperature	0-100°C	0-100°C	0-100°C
Power	230v	400v	400v
Weight	230kg	250kg	270kg
Dimensions (H x W x D)	160 x 82 x 56cm	160 x 82 x 56cm	160 x 82 x 56cm

