

MAC PERMAHOT STATIC

ELECTRICALLY HEATED PRESSURE WASHERS

Permanently Hot Water

- Electrically heated static
- 90°C constant temperature
- Low water consumption
- 415v - 32 Amp supply
- Strong stainless steel construction
- Patented hot water design

UNIQUE TO THE INDUSTRY



KEY SPECIFICATION

Electrically Heated Static

6ltr/min Water Flow

150bar Pressure

90°C Constant Temperature

415v, 32amp Power Supply

PERMAHOT

MAC PERMAHOT STATIC

ELECTRICALLY HEATED PRESSURE WASHERS

PERMAHOT

STANDARD FEATURES

- 90°C Constant Temperature
- Patented 3 x 4kw Solid Element system
- Full stainless steel chassis and cover
- Front and rear chassis protection bars
- 4 large robust wheels for tough terrain
- Professional Interpump with ceramic pistons
- Industrial 1450rpm low rewing electric motor
- Instant stop system
- Stainless steel water tank with low water cut off switch
- Water softener system
- Bypass valve
- Pressure gauge
- Heater on/off switch
- Mains on lamp & heating element lamp
- Heater controlled by thermostat
- 24v low tension safety controls
- Current thermal overload protection
- Stainless steel manual hose reel & stainless steel basket for accessories - Permahot Laser
- Including 15mt hose, 900mm quick release lance and heavy duty trigger



View the Permahot Product Video at
www.permahot.co.uk

	MAC63
Water Flow	6lt per minute
Pressure	150bar, 2200psi
Motor Specification	5.5hp, 1450rpm
Shutdown System	Instant Stop
Temperature	0-90°C Constant
Power	415v, 32amps
Weight	100kg
Dimensions (h x w x d)	51 x 96 x 59cm

The Permahot range utilises our patented 3 x 4kw solid element heating system.

It is now possible to produce 90°C constant heat, on a standard 415v, 32amp power supply.

Perfect for food environments and all conditions where diesel, fumes and large water consumption are major problems.

www.macinternational.co.uk

WASHMASTER
PRESSURE WASHERS

MAC
PRESSURE WASHERS

WASHMASTER RANGE ELECTRICALLY HEATED PRESSURE WASHERS



MAC PERMAHOT LASER



MAC PERMAHOT STATIC



MAC ELEKTRA