

MAC FIX HT

Designed to Utilise On-Site Hot Water

- Up to 85°C inlet temperature
- High temperature Interpump



KEY SPECIFICATION

Cold Water Module

11ltr, 13ltr 18ltr or 23ltr/min
Water Flow

100bar, 160bar or
170bar Pressure

240v or 415v Power Supply



MAC FIX HT



STANDARD FEATURES

- High quality, full stainless steel cabinet
- Professional Interpump with ceramic pistons
- Industrial 1450rpm low revving electric motor
- Automatic stop/start system
- Bypass valve
- Pressure gauge
- Mains on lamp
- 24v low tension safety controls
- Including 10mt hose, lance and heavy duty trigger

OPTIONAL ACCESSORIES

- Plastic or stainless steel water tank
- Frost protection
- Stainless steel floor stand
- Remote control system
- Low pressure chemical injector with twin lance



	MAC13HT	MAC14HT	MAC15HT	MAC16HT
Water Flow	11lt per minute	13lt per minute	18lt per minute	23lt per minute
Pressure	100bar, 1500psi	170bar, 2465psi	160bar, 2320psi	160bar, 1500psi
Motor Specification	3hp, 1450rpm	5.5hp, 1450rpm	7.5hp, 1450rpm	10hp, 1450rpm
Chemical	Low Pressure	Low Pressure	Low Pressure	Low Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Power	240v	415v	415v	415v
Weight	60kg	70kg	80kg	95kg
Dimensions (h x w x d)	40 x 76 x 47cm	40 x 76 x 47cm	40 x 76 x 47cm	40 x 76 x 47cm